

DATE: 23 Oct 00

STATEMENT OF WORK (SOW)  
for  
Inspection and Repair Only As Necessary (IROAN)  
of the  
AN/TPS-59(V)3  
Thermostatic Switch  
NSN 5930-01-146-3651

SOW-03-844-2-89887B-2/1

1. This SOW identifies the work effort that shall be performed by the Contractor to IROAN the AN/TPS-59(V)3 Thermostatic Switch NSN 5930-01-146-3651, part number 7327584G1, CAGE 03538.
2. The attached manuscript has been reviewed and is concurred upon by the following signers:

---

LAWRENCE E HERNDON  
Weapon Systems Manager  
Radar Systems Section (Code 844-2)  
MARCORSYSCOM, Albany, GA

---

VIRGINIA A WILSON  
Team Leader  
Inventory Management Specialist  
(Code 844-2)  
MARCORSYSCOM, Albany, GA

---

RICHARD E JONES  
Team Leader  
Equipment Specialist  
(Code 844-2)  
MARCORSYSCOM, Albany, GA

STATEMENT OF WORK (SOW)  
for  
Inspection and Repair Only As Necessary (IROAN)  
of the  
AN/TPS-59(V)3  
Thermostatic Switch  
NSN 5930-01-146-3651

1.0 Scope. This Statement of Work (SOW) establishes, sets forth tasks and identifies the work efforts that shall be performed by the Contractor to IROAN the AN/TPS-59(V)3 Thermostatic Switch NSN 5930-01-146-3651, part number 7327584G1, CAGE 03538. This document contains requirements to restore the Thermostatic Switch to Condition Code "A." Condition Code "A" is defined as "serviceable/issuable without qualification; new, used, repaired or reconditioned material that is serviceable and issuable to all customers without limitation or restriction, including material with more than six months shelf-life remaining."

1.1 Background. IROAN is defined as "That maintenance technique which determines the minimum repairs necessary to restore equipment components or assemblies to prescribed maintenance serviceability standards by utilizing all available diagnostic equipment and test procedures in order to minimize disassembly and parts replacement."

2.0 Applicable Documents. The following documents form a part of this SOW to the extent specified. Unless otherwise specified, the issues of these documents are those listed in the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto which is in effect on the date of solicitation. In the event of conflict between the documents referenced herein and the contents of this SOW, the contents of this SOW shall be the superseding requirements.

2.1 Military Standards.

MIL-STD-2073-ID	DoD Standard Practice for Military Packaging
MIL-STD-129	DoD Standard Practice for Military Marking

2.2 Other Government Documents and Publications. The latest issues of those documents cited below shall be used.

7327584	Assembly Drawing, Thermostatic Switch
7327584G1	Parts List, Thermostatic Switch

**Military Handbook (For Guidance).**

<b><i>MIL-HDBK-61</i></b>	<b><i>Configuration Management Guidance</i></b>
---------------------------	---

2.3 Industry Standards.

ANSI/ISO/ASQC Q9003-1994      Quality Systems - Model for Quality Assurance in  
Final Inspection and Test

**Industry Standard (For Guidance).**

***ANSI/EIA-649      National Consensus Standard for Configuration  
Management***

{Copies of military standards and specifications are available from the DOD Single Stock Point, Document Automation and Production Service, Building 4/D, 700 Robbins Avenue, Philadelphia, PA 19111-5094, Telephone (215) 697-2179 or DSN 442-2179, or <http://dodssp.daps.mil>. Copies of other government publications required by contractors in connection with specific SOW requirements shall be obtained through the Contracting Officer: Commander, Attn: Contracting Officer (Code 891), Marine Corps Logistics Base, 814 Radford Blvd., Albany, GA 31704-1128, commercial telephone number (229) 639-6761 or DSN 567-6761. Copies of engineering drawings shall be obtained from: Life Cycle Management Center, Attn (Code 851-3), 814 Radford Blvd Suite 20320, Albany GA 31704-0320, commercial telephone number (229) 639-6410 or DSN 567-6410.}

3.0 **Requirements.**

3.1 The Contractor shall repair the Thermostatic Switch strictly in accordance with the requirements as specified in 7327584 and 7327584G1, CAGE 03538. The Contractor shall be responsible for developing test requirements. The Contractor shall be responsible for all parts, materials, labor, facilities, tools, and test equipment necessary to inspect and repair only as necessary the equipment in accordance with this SOW.

3.2 **Packaging, Handling, Storage and Transportation (PHS&T).**

3.2.1 The Contractor shall be responsible for preservation and packaging of items to be delivered under the terms of this SOW. Items being prepared for long-term storage or overseas (OCONUS) shipment shall be in accordance with level "A" requirements of MIL-STD-2073-1D, Appendix A, Table A.VI, Electronic Equipment. Items being prepared for immediate use and domestic (CONUS) delivery shall be in accordance with level "B" requirements. Level "A" preservation and packaging shall normally be required, due to the anticipated long-term storage requirements. Exceptions (items that have a confirmed immediate use within CONUS) will be identified, in writing, by the Weapon System Manger (WSM), Code 844-2.

3.2.2 Marking shall be in accordance with MIL-STD-129.

3.2.3 The Marine Corps will provide the Contractor with the shipping address(es) for delivery of the repaired equipment. The Contractor shall be responsible for arranging for shipment to the pre-designated site(s). The Marine Corps will be responsible for transportation costs associated with shipping the subject equipment to and from the Contractor.

**3.3 Configuration Control.** *The contractor shall apply configuration control procedures to established configuration items. The contractor shall not implement configuration changes to an item's documented performance or design characteristics without prior written authorization. All permanent changes to the form, fit or function of the baseline shall be by Engineering Change Proposal. MIL-HDBK-61 (paragraph 4.2 and Table 4-6) and ANSI/EIA-649 (paragraph 5.3.1) provide guidance for preparing these configuration control documents. If it is necessary to temporarily depart from the authorized configuration, the contractor shall prepare and submit a Request For Deviation. MIL-HDBK-61 (paragraph 4.3 and Table 4-9) and ANSI/EIA-649 (paragraph 5.3.4) provide guidance for preparing these configuration control documents.*

**3.4 Government Furnished Equipment (GFE) and Government Furnished Materiel (GFM).** The Management Control Activity (MCA/Code 827-2) will coordinate Government Furnished Equipment/Government Furnished Materiel (GFE/GFM) requests and maintain a central control system on all government owned assets in the Contractor's possession. The MCA will forward a GFE/GFM Accountability Agreement to the Contractor for signature to establish a chain of custody and identify property responsibilities for Marine Corps assets. The Contractor shall report receipt of all GFE/GFM, and report consumption of GFM to the MCA. The MCA, in conjunction with the WSM, reserve the right to deny any requests for GFE/GFM. Under no circumstances shall such denial form a basis for either work stoppages or delays in delivery.

**3.5 Quality Assurance Provisions.** The Contractor shall provide and maintain a Quality System that, as a minimum, adheres to the requirements of ANSI/ISO/ASQC Q9003-1994, Quality Systems - Model for Quality Assurance in Final Inspection and Test.

**4.0 Reports.** The Contractor shall develop a Test Data Report (TDR), based on test requirements to be developed by the Contractor (in accordance with this SOW), which references this SOW, the NSN, part number, and serial number of the Thermostatic Switch. Upon request, a copy of the TDR shall be submitted electronically (preferred), via regular mail, or facsimile to the WSM. Electronic address is "[MbMatcom844-2@matcom.usmc.mil](mailto:MbMatcom844-2@matcom.usmc.mil)" Mailing address is: Commander, Attn (Code 844-2), Marine Corps Systems Command, 814 Radford Boulevard Suite 20343, Albany, GA 31707-0343. Facsimiles may be sent to (229) 639-5498 or DSN 567-5498, attention Weapons System Manager, Code 844-2.



