

Draft
Maintenance Concept Remains Consistent With Prior
Fiscal Year

STATEMENT OF WORK (SOW)
FOR THE
REBUILD/CONVERSION

OF THE

VT-400 FINAL DRIVE ASSEMBLY
NSN 2520-01-125-5933
NSN-2520-00-438-9020

TO THE

VT-525 FINAL DRIVE ASSEMBLY
NSN 2520-01-463-8091

STATEMENT OF WORK
 FOR THE REBUILD/CONVERSION
 OF THE VT-400 FINAL DRIVE ASSEMBLY
 NSN 2520-01-125-5933/2520-00-438-9020
 TO THE
 VT-525 FINAL DRIVE ASSEMBLY
 NSN 2520-01-463-8091

Table of Contents

Section/Paragraph	Page	
1.0	SCOPE 1	
1.1	Background	1
2.0	APPLICABLE DOCUMENTS	1
2.1	Military Standards	1
2.2	Other Government Standards and Publications	2
2.3	Industry Standards	2
3.0	REQUIREMENTS	3
3.1	General Tasks	3
3.2	Detailed Tasks	4
3.2.1	Phase I- Rebuild/Conversion	4
3.2.2	Phase II- Inspection, Testing and Acceptance	4
3.2.3	Phase III-Packaging, Handling Storage and Transportation (PHS&T)	4
3.3	Configuration Control	4
3.4	Government Furnished Equipment (GFE)/ Government Furnished Material (GFM)	5
3.5	Contractor Furnished Material (CFM)	5
3.6	Quality Assurance Provisions	6
4.0	REPORTS	6
4.1	Monthly Production Status Report	6

**STATEMENT OF WORK
 FOR THE REBUILD/CONVERSION
 OF THE VT-400 FINAL DRIVE ASSEMBLY
 NSN 2520-01-125-5933/2520-00-438-9020
 TO THE
 VT-525 FINAL DRIVE ASSEMBLY
 NSN 2520-01-463-8091**

1.0 SCOPE. This Statement of Work (SOW), along with TM 09674A-25&P/4A establishes, sets forth tasks and identifies the work efforts that shall be performed by the contractor in the rebuild/conversion of the VT-400 Final Drive Assembly, NSN 2520-01-125-5933 and/or NSN 2520-00-438-9020 to the VT-525 Final Drive Assembly configuration, P/N 7010045, NSN 2520-01-463-8091. The assembly will be received in either of two conditions codes "A" or "F". When received in condition code "A" it will be converted to part number P/N 7010045, NSN 2520-01-463-8091, CAGE 0MLM6. If received in condition code "F", the VT-400 Final Drive Assembly will be rebuilt and converted to part number 7010045, NSN 2520-01-463-8091, CAGE 0MLM6. This document contains minimum requirements to restore the VT-400 Final Drive Assembly to Condition Code "A". Condition Code "A" is defined as "serviceable/issuable without qualification, new, used, repaired or reconditioned material which is serviceable and issuable to all customers without limitations or restriction. The rebuild/converted VT-525 Final Drive Assembly is identified as NSN 2520-01-463-8091.

1.1 Background. Rebuild/Conversion is defined as that maintenance technique to restore an item to a standard as near as possible to original or new condition in appearance, performance, and life expectancy. This is accomplished through disassembly of the item; inspection of all parts or components, repair or replacement of worn or unserviceable parts using original manufacturing tolerances and/or specifications and subsequent reassembly of the item. Conversion is defined as the maintenance technique to modify the VT-400 Final Drive Assembly to the VT-525 Final Drive Assembly configuration.

2.0 APPLICABLE DOCUMENTS. The following documents form a part of this SOW to the extent specified. Unless otherwise specified, the issues of these documents are those listed in the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto which is in effect on the date of solicitation. In the event of conflict between the documents referenced herein and the contents of this SOW, the contents of this SOW shall be the superseding requirement.

2.1 Military Standards

MIL-STD-2073-1D	DoD Standard Practice for Military Packaging
MIL-STD-129	DoD Standard Practice for Military Marking

2.2 Other Government Documents and Publications

DoD 4000.25-1-M	Military Standard Requisition and Issue Procedures (MILSTRIP)
DoD 4160.21-M-1	Defense Demilitarization Manual
TM 09674A-25&P/4A	Maintenance Instruction and Repair Parts List Organizational, Intermediate and Depot Assault Amphibious Vehicle Model 7A1 Family Of Vehicles and RAM/RS
TM 2350-45	DMA Standard Procedures
RS 3.4A	Rebuild Standards for the AAVP7A1
TI 990301	Installation and Assembly of the VT 525 Power Plant Assembly Integration Kit (Appendix A)
Engineering Drawing 2600084 CAGE 0MLM6	VT-400 Final Drive Assembly
Engineering Drawing 7010045 CAGE 0MLM6	VT-400 Final Drive Assembly (RAM/RS)
ASTM D 3951	Standard Practice for Commercial Packaging
<u>Military Handbook (For Guidance)</u>	
MIL-HDBK-61	Configuration Management Guidance
2.3 <u>Industry Standard</u>	
ANSI/ISO/ASQC Q 9001-2000	Quality Management Systems-Requirements
<u>Industry Standard (For Guidance)</u>	
ANSI/EIA-649	National Consensus Standards for Configuration Management

Copies of Military Standards and Specifications are available from the DoD Single Stock Point, Document Automation and Production Service, Building 4/D, 700 Robbins Avenue, Philadelphia, PA 19111-5094, commercial telephone number (215) 697-2179 or DSN 442-2179 or <http://www.dodssp.daps.mil>. Copies of other Government documents and publications

requirements shall be obtained through the Contracting Officer: Contracts Department (Code 891), P.O. Drawer 43019, 814 Radford Blvd., Albany, Georgia 31704-3019, commercial telephone number (229) 639-6761 or DSN 567-6761. Copies of Engineering drawings, if applicable, shall be obtained from Supply Chain Management Center, Attn: (Code 583-1), 814 Radford Blvd., STE 20320, Albany, Georgia, 31704-0320, commercial telephone number (229) 639-6476 or DSN 567-6476.

3.0 REQUIREMENTS

3.1 General Tasks. In fulfilling the specified requirements, the contractor shall:

a. Provide materials, labor, facilities, and services necessary to troubleshoot, test, diagnose, engineer, integrate, install, repair, rebuild, and calibrate as required to make the VT-400 Final Drive Assembly fully operational. Upon completion of rebuild/conversion, the VT-400 Final Drive Assembly shall be Condition Code "A". Pre-inspection and acceptance of the VT-400 Final Drive Assembly, NSN 2510-01-125-5933 and/or NSN 2520-00-438-9020 prior to conversion shall be conducted in accordance with TM 09674A-25&P/4A.

b. Marine Corps System Command (MCSC) (PMM143), Albany, Georgia representative shall witness final on-site testing.

c. The contractor shall be responsible for all structural and mechanical requirements associated with the rebuild/conversion of the VT-400 Final Drive Assembly as specified in TM 09674A-25&P/4A and this SOW.

d. Ensure all VT-400 Final Drive Assemblies meet the configuration of Engineering Drawing 7010045, CAGE 0MLM6.

e. All mandatory replacement parts shall be replaced in accordance with TM 09674A-25&P/4A and TI 990301. Economically replacement parts may be reused if they meet the applicable inspection requirements in TM 2350-45. All parts shall be disposed of in accordance with DoD 4160.21-M-1.

3.2 Detailed Tasks. The following tasks describe the different phases for the rebuild/conversion of the VT-400 Final Drive Assembly.

3.2.1 Phase I - Rebuild/Conversion. The contractor shall receive VT-400 Final Drive Assembly for rebuild/conversion. The contractor shall then disassemble the VT-400 Final Drive Assembly into components and conduct the rebuild/conversion process. The contractor shall rebuild/convert components in accordance with the requirements in TM 09674A-25&P/4A and this SOW. The contractor shall, with the exception of GFM, be responsible for supplying all equipment, tools, test equipment, and materials for the conduct of this effort. The contractor shall be responsible for the integration and assembly of all components. The configuration identification for the VT-400 Final Drive Assembly is defined by the specifications annotated on

current revision levels of Engineering Drawing 2600084, CAGE OMLM6 and Engineering Drawing 7010045, CAGE OMLM6.

3.2.2 Phase II - Inspection, Testing and Acceptance. Inspection, testing and acceptance of the VT-400 Final Drive Assembly shall be conducted in accordance with TM 09674A-25&P/4A, RS 3.4A and ANSI/ISO/ASQC Q9001-2000. The contractor will correct any deficiencies discovered.

3.2.3 Phase III - Packaging, Handling, Storage and Transportation (PHS&T)

a. The contractor shall be responsible for preservation and packaging on item(s) being rebuilt under the terms of this statement of work. Items scheduled for long-term storage or shipment to overseas destinations shall be in accordance with Level "A" requirements of MIL-STD-2073-1D, Appendix J.1a, Specialized preservation code "DB". Items scheduled for domestic shipment for immediate use shall be in accordance with the best commercial practices of ASTM D 3951. Items scheduled for overseas shipment for immediate use shall be in accordance with the best commercial practices of ASTM D 3951, Paragraph 6.1, and Export Shipments.

NOTE: Level "A" requirements shall be identified in writing by the Logistics Management Specialist (Code PMM143).

b. Marking for shipment and storage shall be in accordance with MIL-STD-129.

c. The Marine Corps will provide the contractor with the shipping address(es) for delivery of the upgraded equipment, and the contractor shall be responsible for arranging for shipment to the pre-determined site(s). The Marine Corps will be responsible for transportation costs associated with shipping the subject equipment to and from the contractor.

3.3 Configuration Control

a. The contractor shall apply configuration control procedures to established configuration items. The contractor shall not implement configuration changes to an item's documented performance or design characteristics without prior written authorization. Procedures or materials contained in manuals, standards and instructions or engineering drawings/documents define the item's characteristics. If deemed necessary to temporarily depart from the authorized configuration, the contractor shall prepare and submit a Request For Deviation (RFD). MIL-HDBK-61 and ANSI/EIA-649 provide guidance for preparing RFDs.

b. The creation and submission of RFDs shall be accomplished using MEARS CREATE software, which resides at a secure web site, <https://mearsweb.redstone.army.mil>. For the purpose of gaining access to the web site, the contractor shall request user-id and password privileges from the Requiring Office identified in Block 6 of the applicable Contract Data Requirements List. The contractor shall direct technical or functional questions concerning

usage of MEARS CREATE software to the Requiring Office for guidance. The contractor shall notify the Requiring Office by electronic mail when completed MEARS RFDs are ready for formal submission.

3.4 Government Furnished Equipment (GFE)/Government Furnished Materiel (GFM). The Management Control Activity (MCA/Code 571-1) will coordinate GFE/GFM requests and maintain a central control system on all government owned assets in the contractor's possession. The MCA will forward a GFE Accountability Agreement to the Contractor for signature on an annual basis to establish a chain of custody and property responsibility for Marine Corps assets. The contractor is to acknowledge receipt of GFM to the MCA within 15 days of receipt. This can be done by mailing a copy of the DD 1348 to: Materiel Management Department, Management Control Activity (Code 571-1), 814 Radford Blvd., STE 20320, Albany, GA 31704-0320 or faxing to commercial telephone number (229) 639-5498 or DSN 567-5498.

The below listed material is available:

<u>Nomenclature</u>	<u>Part Number</u>	<u>Quantity Per Application</u>
Seal	7010160	1 Ea
Yoke	7010055	1 Ea
Shaft Assembly	7001167	1 Ea

3.5 Contractor Furnished Materiel (CFM). The Contractor may requisition materials as required in the performance of this SOW through the DoD Supply System. DoD 4000.25-1-M (MILSTRIP), Chapter 11, provides guidance to the contractors on the requisitioning process. The decision to utilize CFM procured from the DoD Supply System shall be based upon cost effectiveness, availability of materiel and the required completion/delivery date.

3.6. Quality Assurance Provisions

3.6.1 The performance of the contractor's quality of work performed, materiel provided and documents written shall be subject to in-process review and inspection by the MCSC (PMM143), Albany, Georgia representative during contract performance. Inspection may be accomplished at any work location. The MCSC (PMM143), Albany, Georgia representative shall be permitted to observe the work/tasks accomplishment and/or to conduct inspections at any reasonable hour. Acceptance Tests shall be held in-plant. The MCSC (PMM143), Albany, Georgia representative requires, at a minimum, two weeks notification of the acceptance test to allow for sufficient time for MCSC (PMM143), Albany, Georgia representative to witness acceptance. Inspection by the MCSC (PMM143), Albany, Georgia representative of all acceptance tests, materials and associated lists furnished hereunder does not relieve the contractor from any responsibility regarding defects or other failures to meet the SOW requirements which may be disclosed prior to final acceptance.

3.6.2 The contractor shall provide and maintain a Quality System that, as a minimum, adheres to the requirements of ANSI/ISO/ASQC Q9001-2000. The contractor's work shall be subject to in-process reviews and inspections for compliance with these procedures and standards by a MCSC (PMM143), Albany, Georgia representative. Noncompliance with these quality assurance procedures resulting in degraded quality of work may result in a stop-work order requiring action by the contractor to correct the work performed and to enforce compliance with quality assurance procedures or face contract termination. Notwithstanding such inspection, it shall be the contractor's responsibility to ensure that the entire system meets the performance requirements of this SOW.

4.0 REPORTS. All reports deliverables shall be submitted in hard copy to Marine Corps Systems Command, Attn: (PMM143), 814 Radford Blvd., Suite 20343, Albany Georgia 31704-0343, unless directed otherwise in a Contract Data Requirements List.

4.1 Monthly Production Status Report. A Monthly Production Status Report shall be submitted summarizing the progress and status of the VT-400 Final Drive Assembly.