

STATEMENT OF WORK (SOW)

FOR THE CONVERSION OF THE

**HS-400-3A1 TRANSMISSION
NSN 2520-01-113-6132**

**HS-400-3A1 TRANSMISSION WITH CONTAINER
NSN 2520-01-134-3891**

**HS-400-3A1-1 TRANSMISSION
NSN 2520-01-390-3750**

**HS-400-3A1-1 TRANSMISSION WITH CONTAINER
NSN 2520-01-400-2206**

TO THE

**HS-525 TRANSMISSION
NSN 2520-01-472-3051**

**AND THE HS-525 TRANSMISSION WITH CONTAINER
NSN 2520-01-472-6681**

STATEMENT OF WORK (SOW)
FOR THE CONVERSION OF THE
HS-400-3A1 TRANSMISSION, NSN 2520-01-113-6132
HS-400-3A1 TRANSMISSION WITH CONTAINER, NSN 2520-01-134-3891
HS-400-3A1-1 TRANSMISSION, NSN 2520-01-390-3750
HS-400-3A1-1 TRANSMISSION WITH CONTAINER, NSN 2520-01-400-2206
TO THE
HS-525 TRANSMISSION, NSN 2520-01-472-3051
AND THE HS-525 TRANSMISSION WITH CONTAINER, NSN 2520-01-472-6681

TABLE OF CONTENT

<u>Paragraph/Content</u>	<u>Page</u>	
1.0	Scope	1
1.1	Background	1
2.0	Applicable Document	1
2.1	Military Standards	1
2.2	Other Government Documents and Publications	1
2.3	Industry Standards	3
3.0	Requirements	3
3.1	General Tasks	3
3.2	Detailed Tasks	4
3.2.1	Phase I-Conversion	4
3.2.1.1	Overhaul/Conversion Data Plate	4
3.2.2	Phase II-Inspection, Testing, Acceptance	5
3.2.3	Phase III Packaging, Handling, Storage and Transportation	5
3.3	Configuration Control	6
3.4	Government Furnished Equipment (GFE)/Government Furnished Material (GFM)	6
3.5	Contractor Furnished Material (CFM)	7
3.6	Quality Assurance Provisions	7
4.0	Reports	8

Attachment A GFM Parts Requirement to Convert HS400A1 to HS525

**STATEMENT OF WORK (SOW)
 FOR THE CONVERSION OF THE
 HS-400-3A1 TRANSMISSION, NSN 2520-01-113-6132
 HS-400-3A1 TRANSMISSION WITH CONTAINER, NSN 2520-01-134-3891
 HS-400-3A1-1 TRANSMISSION, NSN 2520-01-390-3750
 HS-400-3A1-1 TRANSMISSION WITH CONTAINER, NSN 2520-01-400-2206
 TO THE
 HS-525 TRANSMISSION, NSN 2520-01-472-3051
 AND THE HS-525 TRANSMISSION WITH CONTAINER, NSN 2520-01-472-6681**

1.0 Scope. This Statement of Work (SOW), along with Draft TM 8F152B-25&P/A dated Oct 98 establishes, sets forth tasks and identifies the work efforts that shall be performed by the contractor in the conversion of the Assault Amphibious Vehicle (AAV) HS-400-3A1 Transmission, HS-400-3A1 Transmission with Container, HS-400-3A1-1 Transmission and the HS-400-3A1-1 Transmission with Container (hereafter referred to as the HS-400 series Transmission) to the HS 525 Transmission and HS-525 Transmission with Container. This document contains minimum requirements for the conversion of the HS-400 series transmission to a Condition Code "A" HS-525 Transmission or HS-525 Transmission with Container. Condition Code "A" is defined as "serviceable/issuable without qualification, new, used, repaired or reconditioned material which is serviceable and issuable to all customers without limitations or restrictions. Upon completion of the conversion, the transmission will be identified as the HS-525 Transmission (NSN) 2520-01-472-3051 or HS-525 Transmission with Container NSN 2520-01-472-6681. Transmission configurations will be without Power Take Off and Hydrostatic Steering Unit.

1.1 Background. Conversion is defined as the maintenance process which disassembles an item only to the extent required to convert/modify it to the new configuration.

2.0 Applicable Documents. The following documents form a part of this SOW to the extent specified. Unless otherwise specified, the issues of these documents are those listed in the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto which is in effect on the date of solicitation. In the event of conflict between the documents referenced herein and the contents of this SOW, the contents of this SOW shall be the superseding requirement.

2.1 Military Standards

MIL-STD-129	DoD Standard Practice for Military Marking
MIL-STD-2073-1D	DoD Standard Practice for Military Packaging

2.2 Other Government Documents and Publications

DoD 4000.25-1-M	Military Standard Requisitioning and Issue Procedures (MILSTRIP)
-----------------	--

DoD 4160.21-M-1	Defense Demilitarization Manual
RS 3.4A	Rebuild Standards for the AAV7A1
TM 2350-45	DMA Standard Procedures
TM-8FI52B-25&P/A, Draft	Power Plant Assembly AAV7A1
MI 2350-25/83	Change Hose and Clamps on the Transmission
MI 2350-25/97	DDM Transducer Relocation
MI 2350-45/99	Retaining Bell Crank on Reverse Steering Mechanism
MI 2350-45/108	Transmission Tube Clamp
TI-990301, Draft	Installation and Assembly of the 525 HP Power Plant Assembly Integration Kit (Appendix A)
ECP M31369	Reduce Slot Opening in Transmission
ECP E5068	Change Engine and Transmission Drain Hose
ECP E5220	Introduction of the Improved, Reliable and Maintainable (IRAM) Transmission
834-002BW	Waiver Transmission Gasket
ECP 5343	Cover, Oil Supply Cast Iron
Engineering Drawing 2600087 CAGE 80064	Transmission Assembly HS-400-3A1
Engineering Drawing 6227600 CAGE 53711	HS-400-3A1-1 (Improved) Transmission Assembly Build-Up
Engineering Drawing 5419069 CAGE 53711	Overhaul/Conversion Data Plate
Engineering Drawing 7010146 CAGE 0MLM6	Transmission Assembly (HS-525)

Engineering Drawing 7010034
CAGE OMLM6

Power Plant Assembly (HS-525)

Engineering Drawing 7010203
CAGE OMLM6

Transmission Identification Plate (HS-525)

ASTM D 3951

Surface Protection Film

Military Handbook (For Guidance)

MIL-HDBK-61

Configuration Management Guidance

2.3 Industry Standards

ANSI/ISO/ASQC Q9002-1994

Quality Systems-Model for Quality Assurance
in Production, Installation and Servicing

Industry Standards (For Guidance)

ANSI/EIA-649

National Consensus Standards for Configuration
Management

Copies of Military Standards and Specifications are available from the DoD Single Stock Point, Document Automation and Production Service, Building 4/D, 700 Robbins Avenue, Philadelphia, PA 19111-5094, commercial telephone number (215) 697-2179 or DSN 442-2179 or <http://www.dodssp.daps.mil>. Copies of other Government documents and publications shall be obtained through the Contracting Officer: Contracts Department (Code 891), P.O. Drawer 43019, 814 Radford Blvd., Marine Corps Logistics Bases, Albany, Georgia 31704-3019, commercial telephone number (229) 639-6761 or DSN 567-6761. Copies of engineering drawings, if applicable, shall be obtained from Supply Chain Management Center, Attn: (Code 583-1), 814 Radford Blvd., STE 20302, Albany, Georgia, 31704-0320, commercial telephone number (229) 639-6476 or DSN 567-6476.

3.0 REQUIREMENTS

3.1 General Tasks. In fulfilling the specified requirements, the contractor shall render, yet not be limited to the following tasks:

a. Provide components, materials, labor, facilities, and services necessary to troubleshoot, test, diagnose, engineer, integrate, install, repair, rebuild, and calibrate as required to make the HS-400 series Transmissions fully operational as the HS-525 Transmission Assembly. Upon completion of the conversion the HS-525 Transmission Assembly shall be Condition Code "A". Preinspection, and acceptance of the HS-400 series Transmission prior to conversion shall be conducted in accordance with Draft TM 8FI52B-25&P/A.

b. Conduct final-on-site testing, which shall be witnessed by Marine Corps Systems Command (MCSC) (PMM143) Albany, Georgia representative.

c. The contractor shall be responsible for all structural, electrical, and mechanical requirements associated with the conversion of the HS-400 series Transmissions as specified in Draft TM 8F152B-25&P/A, RS 3.4A, and this SOW.

d. Ensure all HS-400 series Transmissions meet the configuration of Engineering Drawing 2600087, CAGE 80064. The HS-400 series Transmission will be minus the Hydrostatic Steering Unit (HSU) and Power Take Off (PTO). Remove the torque converter (PN 2600146) from the 400 series transmission, clean, drain, and prepare for storage. Replace with the new HS-525 torque converter (PN 7010161) to be provided as GFM. Request disposition instructions for the torque converter (PN 2600146) from Supply Chain Management Center, Material Management Department, Combat Ground Weapons Branch, Amphibious Assault Section (Code 576-2), 814 Radford Blvd., Suite 20320, Marine Corps Logistics Bases, Albany, Georgia 31704-0320.

e. All mandatory replacement parts shall be replaced in accordance with Draft TM 8F152B-25&P/A, 834-002BW and Draft TI-990301. Economically repairable replacement parts may be reused if they meet the applicable inspection requirements in TM 2350-45. All parts shall be disposed of in accordance with DoD 4160.21-M-1.

3.2 Detailed Tasks. The following tasks describe the different phases for the conversion of the HS-400 series Transmissions to the HS-525 Transmission Assembly.

3.2.1 Phase I-Conversion. The contractor shall receive HS-400 series Transmission for conversion. The contractor shall then disassemble the HS-400 series Transmission into components and conduct the conversion process. The contractor shall reconfigure components in accordance with the requirements in Draft TM-8F152B-25&P/A, Draft TI-990301, and this SOW. The contractor shall be responsible for supplying all equipment, tools, test equipment, and materials, with the exception of GFM (see Attachment A) for the conduct of this effort. The contractor shall be responsible for the integration and assembly of all components. All Modification Instructions (MIs) and Engineering Change Proposals (ECPs), MI 2350-25/83, MI 2350-25/97, MI 2350-45/99, and MI-2350-45/108, ECP M31369, ECP E5068, ECP E5220, and ECP 5343 shall be applied during the conversion process. The existing Transmission Data Plate shall be replaced. Data Plate, Engineering Drawing 7010203, CAGE 0MLM6, shall be manufactured and installed. The configuration identification for the HS-525 Transmission Assembly is defined by the specifications annotated on current revision levels of Engineering drawing 7010146, CAGE 0MLM6.

3.2.1.1 Overhaul/Conversion Data Plate. Upon completion of the conversion process, the contractor shall install Overhaul/Conversion Data Plates, Engineering Drawing 5419060, CAGE 53711, as identified in DMA Standards Procedure 20 of TM 2350-45 on the transmission. The overhaul/conversion data plate shall mark the NSN, part number, serial number, repair contractor, and date the component was completed.

3.2.2 Phase II- Inspection, Testing, Acceptance

a. Upon completion of the conversion process, the contractor shall be required to test each HS-525 Transmission on a dynamometer, to verify system operability. Requirements for the dynamometer test are provided in Draft TM 8F152B-25&P/A. The MCSC (Code PMM143) Albany, GA representatives shall be notified three working days prior to all dynamometer testing, and can witness this testing at his/her discretion. Failure of The HS-525 Transmission to meet the dynamometer test requirements shall be grounds for rejection of the unit. Any units rejected shall be reworked and resubmitted for dynamometer testing and acceptance. The contractor shall be responsible for correcting any deficiencies identified during testing. The MCSC (Code PMM143) representative may require the contractor to repeat tests, or portions thereof, if the original tests fail to demonstrate compliance with this SOW.

b. The HS-525 Transmission Assembly will be assigned a six-digit serial number. Procedures for assigning serial numbers are as follows: The first digit will identify the contractor (A=Albany Ga), (B=Barstow Ca). The next four digits represents the Julian Date in which the transmission was green tagged, cost work center final, (9001). There shall be only one transmission per Julian date at each contractor site. The final digit represents the Model upgrade (E=HS-525 Transmission). Examples - A9001E or B9001E.

c. The performance of the contractor and the quality of work delivered, including all documentation of material written or compiled, shall be subject to in-process review and inspection during performance. Inspection may be accomplished in-plant or at any work site. The MCSC (Code PMM143) representative shall be permitted to observe the work and/or to conduct inspections at any reasonable hour. Final inspection and acceptance shall be at the contractor's facility.

d. Final Inspection, testing and acceptance of each HS-525 Transmission Assembly with/without container shall be conducted in accordance Draft TM-8F152B-25&P/A.

e. Failure to comply with any of the specified requirements listed herein shall be reason for rejection by the MCSC (Code PMM143) Albany representative. The contractor shall, at no additional cost to the Marine Corps, provide the following:

(1) Develop an approach for the correction of all deficiencies.

(2) Upon approval by the MCSC (Code PMM143) Albany, representative, the contractor shall correct the deficiencies and repeat the verification until an acceptable compliance with acceptance test procedure requirements is demonstrated.

3.2.3 Phase III – Packaging Handling Storage and Transportation (PHS&T).

a. Upon conversion completion the Contractor shall be responsible for preservation and packaging of item(s) under the terms of this Statement of Work. Items without containers scheduled for shipment to long term storage or overseas shipment shall be in accordance with

level "A" requirements of MIL-STD-2073-1D Method 54. Items with containers scheduled for shipment to long-term storage or overseas shipment shall be in accordance with Level "A" requirements of MIL-STD-2073-ID, Method 55. Items scheduled for domestic shipment for immediate use shall be in accordance with the best commercial practices of ASTM D 3951. Items scheduled for overseas shipment for immediate use shall be in accordance with the best commercial practices of ASTM D 3951, paragraph 6.1, Export Requirements.

NOTE: Level "A" preservation and packaging shall normally be required due to long-term storage requirements. The Logistics Management Specialist (MCSC, PMM143) shall identify exceptions in writing.

b. Marking for shipment and storage shall be in accordance with MIL-STD-129.

c. The Marine Corps will provide the contractor with the shipping address(es) for delivery of the converted equipment, and the contractor shall be responsible for arranging for shipment to the predesignated site(s). The Marine Corps will be responsible for transportation cost associated with the shipping the subject equipment to and from the contractor.

3.3 Configuration Control

a. The contractor shall apply configuration control procedures to established configuration items. The contractor shall not implement configuration changes to an item's documented performance or design characteristics without prior written authorization. If deemed necessary to temporarily depart from the authorized configuration, the contractor shall prepare and submit a Request For Deviation (RFD). MIL-HDBK-61 and ANSI/EIA-649 provide guidance for preparing RFDs.

b. The creation and submission of RFDs shall be accomplished using MEARS CREATE software, which resides at a secure web site, <https://mearsweb.redstone.army.mil>. For the purpose of gaining access to the web site, the contractor shall request user-id and password privileges from the Requiring Office identified in Block 6 of the applicable Contract Data Requirements List. The contractor shall direct technical or functional questions concerning usage of MEARS CREATE software to the Requiring Office for guidance. The contractor shall notify the Requiring Office by electronic mail when completed MEARS RFDs are ready for formal submission.

3.4 Government Furnished Equipment (GFE)/Government Furnished Materiel (GFM). The Management Control Activity (MCA/Code 573-2) will coordinate GFE/GFM requests and maintain a central control system on all government owned assets in the contractor's possession. The MCA will forward a GFE Accountability Agreement to the Contractor for signature on an annual basis to establish a chain of custody and property responsibility for Marine Corps assets. The contractor is to acknowledge receipt of GFM to the MCA within 15 days of receipt. This can be done by mailing a copy of the DD1348 to Materiel Management Department, Management Control Activity (Code 573-2), 814 Radford Blvd., STE 20320, Albany GA 31704-0320, or faxing a copy to commercial telephone number (229) 639-5498 or DSN 567-5498.

3.4.1 Government Furnished Equipment

a. Each contractor will receive (1) Hydrostatic Steering Unit (HSU) and (1) Power Take Off Unit (PTO) in condition code “A” for the HS 525 transmission conversion process. The HSU and the PTO shall be returned to Marine Corps System Command, (PMM143) Marine Corps Logistics Bases, 814 Radford Blvd., Suite 20343, Albany, Ga 31704-0343 in condition code “A”.

3.4.2 Government Furnished Materiel.

a. Request will be submitted to Supply Chain Management Center, Material Management Department, Combat Ground Weapons Branch, Amphibious Assault Section (Code 576-2), 814 Radford Blvd., STE 20320, Marine Corps Logistics Bases, Albany, Georgia 31704-0320, commercial telephone number (229) 639-5590/91 or DSN 567-5590/91. The below listed material is available:

<u>Nomenclature</u>	<u>Part Number</u>	<u>Quantity Per Application</u>
a. 65 Tooth Gear	710170A	1 Ea
b. 62 Tooth Gear	710203A	1 Ea
c. Reaction Plates (Steel)	206177M	16 Ea
d. Reaction Plates (Poly)	206178D	16 Ea
e. Cover, Oil Supply	2584769-3 (sm)	2 Ea
f. Cover, Oil Supply	2584713-2 (lg)	1 Ea
g. Torque Converter	7010161	1 Ea
h. Parts Requirements List	Appendix A	

3.5 Contractor Furnished Materiel (CFM). The Contractor may requisition materiel as required in the performance of this SOW through the DoD Supply System. DoD 4000.25-1-M (MILSTRIP), Chapter 11, provides guidance to the contractors on the requisitioning process. The decision to utilize CFM procured from the DoD Supply System shall be based upon cost effectiveness, availability of materiel and the required completion/delivery date.

3.6. Quality Assurance Provisions

3.6.1 The performance of the contractor’s quality of work performed, materiel provided and documents written shall be subject to in-process review and inspection by the MCSC (PMM143), Albany, Georgia representative during contract performance. Inspection may be accomplished at

any work location. The MCSC (PMM143), Albany, Georgia representative shall be permitted to observe the work/tasks accomplishment and/or to conduct inspections at any reasonable hour. Acceptance Tests shall be held in-plant. The MCSC (PMM143), Albany, Georgia representative requires, at a minimum, two weeks notification of acceptance test to allow for sufficient time for MCSC (PMM143), Albany, Georgia representative to witness Acceptance. Inspection by the MCSC (PMM143), Albany, Georgia representative of all acceptance tests, materials and associated lists furnished hereunder does not relieve the contractor from any responsibility regarding defects or other failures to meet the SOW requirements which may be disclosed prior to final acceptance.

3.6.2 The contractor shall provide and maintain a Quality System that, as a minimum, adheres to the requirements of ANSI/ISO/ASQC Q9002-1994. The contractor's work shall be subject to in-process reviews and inspections for compliance with these procedures and standards by MCSC (PMM143), Albany, Georgia representative. Noncompliance with these quality assurance procedures resulting in degraded quality of work may result in a stop-work order requiring action by the contractor to correct the work performed and to enforce compliance with quality assurance procedures or face contract termination. Notwithstanding such inspection, it shall be the contractor's responsibility to ensure that the entire system meets the performance requirements of this SOW.

4.0 Reports. All report deliverables shall be submitted in hard copy to Marine Corps Systems Command, Attn: (PMM143), 814 Radford Blvd, Suite 20343, Albany Georgia 31704-0343, unless directed otherwise in a Contract Data Requirements List.

4.1 Monthly Production Status Report. A monthly Production Status Report shall be submitted summarizing the progress and status of the HS 525 Transmission Assembly.

Government Furnished Materiel
Parts Requirement to convert HS400A1 to HS525

Fig No.	Item No.	Part Number	Description	UM	IN UNIT	box total
6-28	1	MS35764-1295	Bolt, self-locking, (HS 525 only)	ea	8	88
6-28	10	1281976	Washer, flat	ea	26	286
6-28	11	MS51968-8	nut, plain, hex	ea	2	22
6-28	12	MS27183-14	Washer, flat (HS 525 only)	ea	2	22
6-28	14+	2584399	Gasket	ea	1	11
6-28	15+	MS28775-111	Packing	ea	1	11
6-28	16	MS28775-113	Packing	ea	1	11
6-28	17+	MS28775-116	Packing	ea	1	11
6-28	18	MS28775-123	Packing	ea	2	22
6-28	2	10910174-3	WASHER FLAT	ea	8	88
6-28	4	2584199	Gasket	ea	1	11
6-28	6+	2601020	Grommet	ea	1	11
6-28	7+	2601053	Grommet	ea	1	11
6-28	8+	2601019	Grommet	ea	1	11
6-28	9	MS35764-1297	Bolt, self-locking	ea	26	286
Fig No.	Item No.	Part Number	Description	UM	IN UNIT	box total
6-29	1	MS35764-1295	Bolt, self-locking	ea	8	88
6-29	10	2584543	Gasket	ea	2	22
6-29	2	10910174-3	Washer, flat	ea	8	88
6-29	4	2584576	Gasket	ea	2	22
6-29	5	2587662	Ring	ea	2	22
6-29	7	MS35764-1297	Bolt, self-locking	ea	56	616
6-29	8	10910174-3	Washer, flat	ea	56	616
Fig No.	Item No.	Part Number	Description	UM	IN UNIT	box total
6-37	30	MS28775-223	Packing	ea	1	11
6-37	33	MS35764-1295	Screw, self-locking	ea	4	44
6-37	56	MS28775-219	Packing	ea	1	11
6-37	71	MS27183-14	Washer, flat (HS 525 only)	ea	3	33
6-37	89	MS27183-14	Washer, flat (HS 525 only)	ea	2	22
6-37	91	2584302	Gasket	ea	1	11
6-37	88	MS35764-1293	Bolt, self-locking, (HS 525 only)	ea	2	22
Fig No.	Item No.	Part Number	Description	UM	IN UNIT	box total
6-50	10	MS27183-12	Washer, Flat	ea	14	154
6-50	12	7010256	Gasket	ea	1	11
6-50	9	B1821BH031C300N	Bolt, Machine (HS525 only)	ea	14	154
Fig No.	Item No.	Part Number	Description	UM	IN UNIT	box total
6-51	2	MS51095-335	Bolt, Self, Locking (HS525)	ea	7	77
6-51	3	MS27183-12	Washer, Flat	ea	7	77
6-51	5	2588664	Gasket	ea	1	11
Fig No.	Item No.	Part Number	Description	UM	IN UNIT	box total
6-53	10	MS35764-1293	Screw, self-locking	ea	8	88
6-53	13	2584303	Gasket, non-asbestos	ea	1	11
6-53	2	MS90725-71	Screw, cap (HS 525 only)	ea	4	44
6-53	24	MS21318-8	Screw, drive	ea	4	44
6-53	25	7010203	Plate, identification (HS 525 only)	ea	1	11
6-53	5	MS28775-216	Packing, performed	ea	2	22
6-53	6	MS28775-114	Packing, performed	ea	2	22
6-53	7	MS28775-110	Packing, performed	ea	2	22
6-53	8	MS28775-214	Packing, performed	ea	1	11
6-53	9	MS28775-230	Packing, performed	ea	1	11
Fig No.	Item No.	Part Number	Description	UM	IN UNIT	box total
6-54	10	MS35307-308	Screw, cap (HS 525 only)	ea	4	44
6-54	11	MS27183-10	Washer, flat	ea	4	44
6-54	13	2584133	Gasket	ea	1	11
6-54	2	MS35307-308	Screw, cap (HS 525 only)	ea	4	44
6-54	3	MS27183-10	Washer, flat	ea	4	44
6-54	5	2584033	Gasket	ea	1	11
Fig No.	Item No.	Part Number	Description	UM	IN UNIT	box total
6-60	16	MS35764-1295	Bolt, self-locking	ea	7	77
6-60	17	2584713-2	Cover, oil supply	ea	1	11

Government Furnished Material
Parts Requirement to convert HS400A1 to HS525

6-60	18	2584378	Gasket	ea	1	11
6-60	2	MS35764-1297	Bolt, self-locking, (HS 525 only)	ea	12	132
6-60	22	MS28778-6	Packing, performed	ea	2	22
6-60	27	MS35764-1295	Bolt, self-locking, (HS 525 only)	ea	7	77
6-60	28	MS27183-14	Washer, Flat	ea	4	44
6-60	3	MS27183-14	Washer, Flat	ea	12	132
6-60	30	2584380	Gasket	ea	1	11
6-60	31	MS35764-1295	Bolt, self-locking	ea	6	66
6-60	32	25847169-3	Cover, oil supply	ea	1	11
6-60	33	2584379	Gasket	ea	1	11
6-60	37	MS28778-6	Packing, performed	ea	2	22
6-60	38	2587067	Ring, retaining	ea	1	11
6-60	39	MS35764-1293	Bolt, self-locking	ea	6	66
6-60	40	10910174-3	Washer, Flat	ea	6	66
6-60	42	2584414	Gasket	ea	1	11
Fig No.	Item No.	Part Number	Description	UM	IN UNIT	box total
6-64	10	MS35764-1297	Bolt, Self locking, (HS525 ONLY)	ea	6	66
6-64	11	MS27183-14	Washer, Flat	ea	6	66
6-64	2	MS35764-1297	Bolt, Self locking, (HS525 ONLY)	ea	6	66
6-64	21	MS35764-1297	Bolt, Self locking, (HS525 ONLY)	ea	6	66
6-64	22	MS27183-14	Washer, Flat	ea	6	66
6-64	29	MS35764-1297	Bolt, Self locking, (HS525 ONLY)	ea	6	66
6-64	3	MS27183-14	Washer, Flat	ea	6	66
6-64	30	MS27183-14	Washer, Flat	ea	6	66
6-64	37	MS35764-1297	Bolt, Self locking, (HS525 ONLY)	ea	6	66
6-64	42	MS27183-14	Washer, Flat	ea	6	66
Fig No.	Item No.	Part Number	Description	UM	IN UNIT	box total
6-66	11	MS27183-14	Washer, Flat	ea	4	44
6-66	3	2584769-3	Cover, Oil Supply (HS525)	ea	1	11
6-66	1	2587067	Ring, retaining	ea	1	11
6-66	10	MS35764-1295	Bolt, self-locking, (HS 525 only)	ea	4	44
6-66	13	2584380	Gasket	ea	1	11
6-66	14	MS51045-43	Setscrew	ea	1	11
6-66	18	MS35764-1299	Bolt, self-locking, (HS 525 only)	ea	6	66
6-66	19	MS27183-14	Washer, Flat	ea	6	66
6-66	2	MS35764-1295	Bolt, self-locking	ea	6	66
6-66	21	2584381	Shim	ea	2	22
6-66	23	2584342	Shim	ea	2	22
6-66	24	8340190	Bearing, roller	ea	2	22
6-66	28	MS35764-1307	Bolt, self-locking	ea	3	33
6-66	29	10910174-3	Washer, Flat	ea	3	33
6-66	30	MS35764-1297	Bolt, self-locking	ea	31	341
6-66	31	10910174-3	Washer, Flat	ea	31	341
6-66	33	258304	Gasket	ea	1	11
6-66	4	2584379	Gasket	ea	1	11
Fig No.	Item No.	Part Number	Description	UM	IN UNIT	box total
6-72	2	MS27183-14	Washer, flat (HS 525 only)	ea	5	55
6-72	4	7010259	Gasket	ea	1	11
Fig No.	Item No.	Part Number	Description	UM	IN UNIT	box total
6-86	14	2584321	Shim	ea	1	11
6-86	15	2584321	Shim	ea	1	11
6-86	16	M2923	Bearing, cone	ea	1	11
6-86	20	211601	Bearing spacer	ea	1	11
6-86	21	M2923	Bearing, cone	ea	1	11
6-86	29	212327A	Separator spring	ea	4	44
6-86	31	206178D	Reaction plate (HS 525 only)	ea	8	88
6-86	33	206177M	Friction plate (HS 525 only)	ea	8	88
6-86	34	M2923	Bearing, cone	ea	1	11
6-86	38	211601	Bearing spacer	ea	1	11
6-86	39	M2923	Bearing, cone	ea	1	11
6-86	4	7010234	Spur gear (HS 525 only)	ea	1	11

Government Furnished Materiel
Parts Requirement to convert HS400A1 to HS525

6-86	47	212327A	Separator spring	ea	4	44
6-86	49	206178D	Reaction , Plate (HS525 ONLY)	ea	8	88
6-86	51	206177M	Friction plate (HS 525 only)	ea	8	88
6-86	54	M2074Q	Packing	ea	1	11
6-86	56	M-1904-BB	Piston ring	ea	1	11
6-86	57	M-1904-BB	Piston ring	ea	1	11
6-86	58	A2622AD	Retaining ring	ea	1	11
6-86	60	A2622AD	Retaining ring	ea	1	11
6-86	62	7010126	Seal cast iron	ea	3	33
6-86	64	M2074CH	Gasket	ea	1	11
Fig No.	Item No.	Part Number	Description	UM	IN UNIT	box total
6-91	52	7010126	Seal cast iron	ea	3	33
Fig No.	Item No.	Part Number	Description	UM	IN UNIT	box total
6-94	5	7010235	Spur gear (HS 525 only)	ea	1	11
6-94	53	7010126	Seal cast iron	ea	3	33

